

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/013409 A1

(51) International Patent Classification⁷: **H01M 10/48**,
H02J 7/00

(21) International Application Number:
PCT/NZ2004/000141

(22) International Filing Date: 2 July 2004 (02.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/484,571 2 July 2003 (02.07.2003) US

(71) Applicant (for all designated States except US): **IVEN-
SYS ENERGY SYSTEMS (NZ) LIMITED [NZ/NZ]; 39
Princess Street, Christchurch, 8004 (NZ).**

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ANBUKY, Adrian,
H [NZ/NZ]; 23 Heath Street, Christchurch, 8005 (NZ).
HUNTER, Phillip [NZ/NZ]; C/o Invensys Energy Sys-
tems, 39 Princess Street, Christchurch, 8004 (NZ).**

(74) Agent: **BALDWINS; PO Box 5999, Wellesley Street,
Auckland, 1001 (NZ).**

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: BATTERY FLOAT MANAGEMENT



(57) Abstract: The invention relates to a new VRLA battery float model. The model covers the steady state and transient float charge behaviour of both positive and negative electrodes. Backup analysis verifies the internal polarisation distribution for a conventional 2V-cell polarisation behaviours can be identified without the need for a physical reference electrode. The estimated individual electrode polarisation allows early detection of common failure modes like negative plate discharge as well as a reference for float voltage optimisation. Furthermore, the positive polarisation relating to minimum grid corrosion may be correlated with the occurrence of the peak of a "Tafel" like resistance used by the model. The model encourages utilisation of low signal perturbation for testing a cell's state of health and state of charge conditions while at float.

WO 2005/013409 A1